



**装配例**

**型式例**

截面图	材料	温度范围	速度	特点	代号
	NBR	-30至100	1	外骨架紧配合，防尘效果好，双唇防尘油封	F7
	FKM	-20至200			
	PU	-35至100			

  

尺寸	公差
φ D1	H8
L1	±0.2

d	D	H	L	d	D	H	L	d	D	H	L	d	D	H	L
10	20	5	7	38	50	7	10	70	84	8	11	130	146	9	12
14	24	5	7	40	52	7	10	70	85	7	10	140	160	10	14
16	26	5	7	40	60	7	10	75	89	8	11	145	165	10	14
18	30	6	9	45	55	7	10	75	95	7	10	150	170	10	14
19	26	5	7	45	57	7	10	80	94	8	11	155	175	10	14
20	32	6	9	45	65	7	10	80	94	8	12	160	180	10	14
22	32	6	9	50	62	7	10	80	94	8	11	170	190	10	14
22	34	6	9	55	65	7	10	85	99	8	11	175	195	10	14
25	37	6	9	55	69	8	11	90	104	8	11	180	205	12	17
25	37	6	9	55	75	7	10	95	109	8	11	200	225	12	17
28	40	6	9	56	70	8	11	100	114	8	11	220	245	12	17
30	42	6	9	60	70	5	7	105	121	9	12	225	250	12	17
32	44	7	10	60	70	7	10	110	126	9	12	230	255	12	17
32	52	8	11	60	74	8	11	112	128	9	12	236	261	12	17
34	46	7	10	63	77	8	11	115	131	9	12	250	275	12	17
35	47	7	10	65	79	8	11	120	136	9	12				
35	55	7	10	65	85	7	10	125	141	9	12				
36	48	7	10	70	80	7	10	130	146	9	12				